

## STANDARD FEATURES

| 2017 MODELS              | RS-9                      | U-12                      | U-14                      | U-19                      | LS-20                     | U-23                      | U-24                      | U-24GN                    |
|--------------------------|---------------------------|---------------------------|---------------------------|---------------------------|---------------------------|---------------------------|---------------------------|---------------------------|
| Maximum Payload          | 1,950 lbs.                | 4,500 lbs.                | 10,000 lbs.               | 10,000 lbs.               | 4,500 lbs.                | 9,500 lbs.                | 15,000 lbs.               | 15,000 lbs.               |
| Axle Rating              | 3,500 lbs.                | 1 x 7,000 lbs.            | 2 x 7,000 lbs.            | 2 x 7,000 lbs.            | 2 x 3,500 lbs.            | 2 x 7,000 lbs.            | 3 x 7,000 lbs.            | 3 x 7,000 lbs.            |
| Trailer Weight           | 1,050                     | 2,100                     | 3,600                     | 4,000                     | 2,500                     | 4,500                     | 5,400                     | 6,000                     |
| Overall Width            | 94"                       | 82"                       | 102"                      | 102"                      | 102"                      | 102"                      | 102"                      | 102"                      |
| Overall Length           | 14'                       | 15'7"                     | 19'6"                     | 23'8"                     | 24' 9"                    | 27' 4"                    | 28' 4"                    | 33'8"                     |
| Loading Surface Area     | 72" x 9'                  | 60" x 10'10"              | 80" x 14'                 | 80" x 18'                 | 80" x 19'                 | 80" x 22'                 | 80" x 23'                 | 80" x 23'                 |
| Deck Surface             | Treated Pine              | Treated Pine              | Treated Pine              | Treated Pine              | Treated Pine              | Treated Pine              | Hardwood                  | Hardwood                  |
| Lifting Device           | Hydraulic w/ Elec. Assist | Hydraulic w/ Elec. Assist | Hydraulic w/ Elec. Assist | Hydraulic w/ Elec. Assist | Hydraulic w/ Elec. Assist | Hydraulic w/ Elec. Assist | Hydraulic w/ Elec. Assist | Hydraulic w/ Elec. Assist |
| Suspension               | Single Axle Torsion       | Single Axle Torsion       | Twin Axle Torsion         | Twin Axle Torsion         | Twin Axle Torsion         | Twin Axle Torsion         | Tri-Axle Torsion          | Tri-Axle Torsion          |
| Electric Brakes          | Optional                  | Standard                  | Standard                  | Standard                  | Standard                  | Standard                  | Standard                  | Standard                  |
| Wheel Size               | 14"                       | 16"                       | 16"                       | 16"                       | 14"                       | 16"                       | 16"                       | 16"                       |
| Hitch Size               | 2"                        | 2 - 5/16"                 | 2 - 5/16"                 | 2 - 5/16"                 | 2"                        | 2 - 5/16"                 | Pintle                    | Gooseneck                 |
| Systems & Storage Box    | Standard                  | Standard                  | Standard                  | Standard                  | Standard                  | Standard                  | Standard                  | Standard                  |
| Lighting                 | LED                       | LED                       | LED                       | LED                       | LED                       | LED                       | LED                       | LED                       |
| Welded D-Rings           | N/A                       | 4                         | 6                         | 6                         | N/A                       | 6                         | 6                         | 6                         |
| Tie Down Chain Key Slots | -                         | (4) 2/Side-Frt & Rear     | (4) 2/Side-Frt & Rear     | (4) 2/Side-Frt & Rear     | -                         | (4) 2/Side-Frt & Rear     | (4) 2/Side-Frt & Rear     | (4) 2/Side-Frt & Rear     |
| Battery                  | Group 31                  | Group 31                  | Group 31                  | Group 31                  | Group 31                  | Group 31                  | Group 31                  | Group 31                  |
| Stake Bed Pockets        | Standard                  | Standard                  | Standard                  | Standard                  | Standard                  | Standard                  | Standard                  | Standard                  |
| Safety Lock              | N/A                       | Standard                  | Standard                  | Standard                  | N/A                       | Standard                  | Standard                  | Standard                  |
| Warranty                 | 1 Year                    | 1 Year                    | 1 Year                    | 1 Year                    | 1 Year                    | 1 Year                    | 1 Year                    | 1 Year                    |

## FEATURES & BENEFITS

### NO RAMP ADVANTAGES

- Eliminate injuries caused by heavy ramps such as pulled back muscles, smashed feet, and severed fingers that lead to worker comp claims or law suits.
- Save time & money as loading/unloading can be done with-or-without tow vehicle being attached.
- Avoid equipment damage as low approach angle protects equipment from damage caused by falling off ramps during loading and unloading.

### LOW APPROACH ANGLE

- Ability to load any low clearance equipment quickly and safely due to low approach angle.
- Applications: Skid Steers, Scissor Lifts, Fork Lifts, Construction, Farming, Industrial Cleaning Equipment, plus so much more...

### LOCKING MECHANISM

- For assured safety of load, in case of accidental hydraulic line damage.

### LED RUBBER MOUNTED LIGHTING

- Better visibility for safety, and low voltage draw for battery life.

### ADJUSTABLE COUPLER

- Allows for any truck in the fleet to do the towing.

### AUXILIARY RECEIVER

- Used for winch mount and other needs.

### EASY ACCESS GREASE ZERKS

- Deck side grease zerks for axle pins, and fender hinges.

### FACTORY MOLDED WIRE HARNESS

- All connections use molded components for long life operation

### BUILT-IN THEFT PREVENTION

- Frees up time and reduces theft exposure Lower trailer, lock it, and leave it!

### NO JACK NEEDED FOR TIRE CHANGES

- Reduces time with added safety. Break lug nuts loose, apply blocks under each rear corner of trailer, and lower unit to raise tires off the ground.

### TORSION AXLE

- Superior ride and long life

### STAKE BED POCKETS WITH RUB RAIL

- Provides additional tie down locations, framing-or-racking opportunity, and added main frame strength.

### 15' EXTENSION CORD CONTROL MODULE

- Allows for activation of trailer at the systems box, or up to 15' away.

### COURTESY LIGHTING

- Deck side and systems box courtesy lighting on all U-Series Models.

## OPTIONS AVAILABLE FOR ALL MODELS

- Custom Colors
- Military CARC Coating
- Wireless Remote Key Fob
- Spare Tire
- Spare Tire Rack
- Aluminum Custom Wheels
- Mobile D-Rings
- Trailer Deck Mounted Receiver
- Pintle Hitch
- Winch Plate
- Winch
- Solar Trickle Charger
- 10amp On-Board Battery Charger
- Hardwood Decking
- Diamond Plate Steel Decking
- Electric/Hydraulic Jack Stand
- Drum Surge Brakes

Visit [NoRamp.com](http://NoRamp.com) to See NoRamp in Action ■ 30400 CR-2 Granger, IN 46530 ■ Phone: (574) 206-1331 Fax: (574) 262-9012



2017

# www.NoRamp.com

PATENTED TILT TRAILERS

**ELIMINATE INJURIES! • SAVE TIME & MONEY! • AVOID EQUIPMENT DAMAGE!**

