

JULIU DE ROME PATENTED TILT TRAILERS P.COM

ELIMINATE INJURIES! - SAVE TIME & MONEY! - AVOID EQUIPMENT DAMAGE!



STANDARD FEATURES U-23 U-24GN **2019 MODELS** RS-9 U-12 U-13 U-14 U-19 CH-20 LS-20 U-23GN U-24 Maximum Payload 1,950 lbs. 4,500 lbs. 7,000 lbs. 10,000 lbs. 10,000 lbs. 8,000 lbs. 4,500 lbs. 9,500 lbs. 9,500 lbs. 15,000 lbs. 15,000 lbs. Axle Rating 3,500 lbs. 1 x 7,000 lbs. 1 x 10,000 lbs. 2 x 7,000 lbs. 2 x 7,000 lbs. 2 x 6,000 lbs 2 x 3,500 lbs 2 x 7,000 lbs 2 x 7,000 lbs 3 x 7,000 lbs 3 x 7,000 lbs Trailer Weight 1,050 lbs 2,500 lbs 3,000 lbs. 3,600 lbs 4,000 lbs 3,800 lbs 2,500 lbs 4,500 lbs 4,500 lbs 5,400 lbs 6,000 lbs Overall Width 94" 82" 102" 102" 102" 102" 102" 102" 102" 102" 102" 14' 27' 4" Overall Length 15' 7" 16' 7" 19' 6" 23' 8" 24' 3" 24' 9" 33' 9/16" 28' 4" 34' 8" Loading Surface Area 72" x 9 60" x 10'10' 70" x 11 80" x 14' 80" x 18 80" x 19' 80" x 19' 80" x 22 80" x 22 80" x 23 80" x 23 Deck Surface Treated Pine Treated Pine Treated Pine Hardwood Treated Pine Treated Pine Treated Pine Treated Pine Treated Pine Hardwood Hardwood Lifting Device Hydraulic w/ Elec. Assist Hydraulic w/ Elec. Suspension Single Axle Torsion Single Axle Torsion Twin Axle Torsion Tri-Axle Torsion Tri-Axle Torsion Electric Brakes Optional Standard Wheel Size 14" 16" 16" 16" 16" 15" 15" 16" 16" 16" 16" 2" 2 - 5/16" 2 - 5/16" 2" Hitch Size 2 - 5/16" 2 - 5/16" 2 - 5/16" 2 - 5/16" Gooseneck Pintle Gooseneck Systems & Storage Box Standard Lighting LED N/A N/A N/A Welded D-Rings 6 6 6 6 6

Group 31

Standard

Standard

1 Year

FEATURES & BENEFITS

NO RAMP ADVANTAGES

Banjo Hole Cut Outs

Stake Bed Pockets

Battery

Safety Lock

Warranty

Eliminate Injuries caused by heavy ramps such as pulled back muscles, smashed feet, and severed fingers that lead to worker comp claims or lawsuits.

A Multitude of

Group 31

Standard

N/A

1 Year

Group 31

Standard

Standard

1 Year

- Save Time & Money as loading/unloading can be done with-or-without tow vehicle being attached.
- Avoid Equipment damage as low approach angle protects equipment from damage caused by falling off ramps during loading and unloading.

LOW APPROACH TILT TRAILER ANGLE

- Ability to load any low clearance equipment quickly and safely due to low approach angle.
- Applications: Skid Steers, Scissor Lifts, Fork Lifts, Construction, Farming, Industrial Cleaning Equipment, plus so much more...

LOCKING MECHANISM

 For assured safety of load, in case of accidental hydraulic line damage.

GOOSENECK

 Our Twin Axle U-23 and Tri-Axle U-24 are available in Goosenck configurations.

LED RUBBER MOUNTED LIGHTING

(4) 2/Side-Frt & Rear (4) 2/Side-Frt & Rear (4) 2/Side-Frt & Rear (4) 2/Side-Frt & Rear

Group 31

Standard

Standard

1 Year

Better visibility for safety, and low voltage draw for battery life.

Group 31

Standard

Standard

1 Year

AUXILIARY RECEIVER

Used for winch mount and other needs.

EASY ACCESS GREASE ZERKS

Deck side grease zerks for axle pins, and fender hinges.

PROTECTED WIRE HARNESS

 Harness runs through 3" steel center channel reducing maintenance costs and lighting failures.

BUILT-IN THEFT PREVENTION

 Lower trailer, engage safety lock, lock systems box, and prevent theft.

ENCLOSURES

All U-Series Trailers are available with aluminum enclosures.

TORSION AXLE

Superior ride and long life

ADJUSTABLE COUPLER

Standard

Group 31

Standard

Standard

1 Year

Allows for any truck in the fleet to do the towing.

Group 31

Standard

N/A

1 Year

Group 31

Standard

Standard

1 Year

NO JACK NEEDED FOR TIRE CHANGES

Reduces time with added safety. Break lug nuts loose, apply blocks under each rear corner of trailer, and lower unit to raise tires off the ground.

STAKE BED POCKETS WITH RUB RAIL

Provides additional tie down locations, framing-or-racking opportunity, and added main frame strength.

15' EXTENSION CORD CONTROL MODULE

 Allows for activation of trailer at the systems box, or up to 15` away.

AMP METER W/BATTERY LIFE INDICATOR

To confirm charging from tow vehicle, and show battery charge status.

SYSTEMS BOX MECHANICAL COVER

Protects Battery, Pump/Motor from carelessly thrown in tie down staps and tools.

AVAILABLE OPTIONS

Group 31

Standard

Standard

1 Year

Group 31

Standard

Standard

1 Year

Custom Colors

(4) 2/Side-Frt & Rear (4) 2/Side-Frt & Rear (4) 2/Side-Frt & Rear (4) 2/Side-Frt & Rear

Group 31

Standard

Standard

1 Year

- Wireless Remote Kev Fob
- Spare Tire
- Spare Tire Rack
- Aluminum Custom Wheels
- Mobile D-Rings
- Pintel Hitch
- Winch Plate
- Winch
- Solar Trickle Charger
- 10amp On-Board Battery Charger
- Hardwood Decking
- Diamond Plate Steel Decking
- Electric/Hydraulic Jack Stand
- Drum Surge Brakes

Visit NoRamp.com to See NoRamp in Action Phone: (574) 206-1331